

FEMA recommends that flooded areas be cleaned up as quickly as possible in order to dry out the area and reduce mold contamination.

Use Stall DRY to assist in drying up moisture that remains after the bulk of the water from a flood has been removed.

With the ability to **absorb** up to **130%** of its own weight in liquid, Stall DRY will **remove** unwanted **moisture** and dry out the treated area and will also **suppress odors** found in liquids, leaving a cleaner, fresher and **healthier environment**.

Stall DRY can be used on wood, concrete and other sub-floor materials in flooded basements, rooms and garages.

DIRECTIONS FOR USE:

- **1.** Remove all excess water with water vac, mop or other suitable device
- **2.** Once the bulk of the water has been removed, apply up to 1/4 inch of Stall DRY on top of the floor
- 3. Let sit for up to 24 hours
- 4. Sweep up
- 5. Dispose of used material

* If moisture and/or odor still remains, re-apply Stall DRY and allow to sit for up to an additional 24 hours. If absolutely necessary, repeat once again.

Please note:

Stall DRY is an all natural product and can safely be disposed of at landfill sites.

For carpeted areas:

In order to dry the surface under wet carpet, remove all carpeting and have cleaned and dried by professional carpet service before re-installing. Apply Stall DRY to either wood, concrete or other sub-floor materials, as described above.

A 40 lb bag of Stall DRY will cover an area of up to 100 ft.^2

Absorbent Products Ltd. 724 East Sarcee Street Kamloops, BC V2H 1E7 info@absorbentproductsltd.com 800-667-0336